

EARTHING & LIGHTNING PROTECTION • STANDARD

Copper Bonded Solar Earthing Rod (16mm x 1 Meter)

Indicative Rate: ₹ 300 / Pcs

GST Extra as applicable • Note: 16mm Diameter, 1 Meter Length

Minimum Order Qty: 1 Pcs • **Model Ref:** SSE-IM-21-STANDARD

Product Description

16mm x 1 Meter solid earthing electrode rod for safe fault current dissipation in solar power plants. Protects inverters and structures from electrical faults. GST Extra.

Technical Parameters & Reference Metadata

Catalog Serial / SKU	SL #21 / SSE-IM-21
Category	Earthing & Lightning Protection
Brand / Make	Standard
Product Classification	Copper Bonded Earthing Rod
Rated Capacity / Size	16mm Dia x 1 Meter
Technology / Standard	Solid Copper-Bonded Electrode
Material / Build Ref	Includes Brass Saddle Clamp
Original Sheet Reference	EARTING ROD 16MM - 1 Metre
Warranty Guidance	High fault-current conductivity

Key Highlights

- 16mm Diameter x 1 Meter Solid Rod
- Protective Fault & Surge Dissipation
- Saves Inverter & Structure Assets
- Low Contact Resistance Copper Coat

Bihar Headquarters — Patna
Near Mannat Enclave, Kailash Nagar, Bhupatipur Road, Mithapur, Patna, Bihar - 800020
Phone: +91 8235441292 | +91 9304372912 | srishti@srishtisolarenergy.in

West Bengal Branch — Dankuni
WB Desk, Maa Sharda Stationery Shop, Monoharpur, Himnagar, Dankuni, Kolkata - 712311
Phone: +91 9006145811 | info@srishtisolarenergy.in

Published by SRISHTI SOLAR ENERGY
(https://srishtisolarenergy.com)

Prices exclude GST and are subject to order volume & quotation confirmation.